



Novapro PE Metal Wrap

Volatile Corrosion Inhibitor

Pro Forma DATA SHEET

FABRIC SPECIFICATIONS

WEIGHT 2.9 oz/yd² (98 g/m²)
 COLOUR Volatile Corrosion Inhibitor Colours (White, Blue, Clear)
 PRINTING Up to 4 colors, in widths of 120" or less. Over 120", 3 colors

PERFORMANCE

GRAB TENSILE	Warp 87 lb 387 N	Weft 72 lb 320 N	ASTM D5034-01
TRAPEZODIAL TEAR	Warp 32 lb 142 N	Weft 27 lb 120 N	ASTM D5587-03
MULLEN BURST	147 psi 1013 kPa		ASTM D3786-01
BEACH PUNCTURE	18 Joules		Tappi T-803om99
PLIABILITY	- 40° C (- 40° F)		
OUTDOOR WEATHERING	> 80% strength retention after 1 year outdoor exposure		

ROLL SPECIFICATIONS

CORES 3" (76.2mm), 4 inch (101.6 mm) or 5 inch (127 mm) I.D.
 WIDTH Up to 144 inches (-0 , + 0.5) as ordered, 3.66 m (-0, +12 mm)
 LENGTH Minimum 300 yds/roll (274 m); up to 1500 yds/roll (1372 m)

These values are typical data and are not intended as limiting specifications.

FK2008(98 gsmPE)
 Rev New 8/14/2008

Engineered Coated Products
 Brantford, ON Langley, BC Hawkesbury, ON Truro, NS
 1-888-353-9421 1-888-894-6725 1-800-465-5597 1-800-565-2000