

NOVA-SEAL^{II}[®]

Premium Roofing Underlayment

The Best Choice In Weatherproofing Systems

"Feel The Difference"



(Illustration demonstrates slip resistant textured surface)

Strength, Safety, Durability

Nova-Seal[®] II is a premium roofing underlayment that delivers exceptional long term weather barrier performance compared to both traditional asphalt felt products and other synthetic underlayments.

Nova-Seal[®] II is a 100% synthetic underlayment with slip-resistant coatings on both sides. The bottom is designed to reduce slippage between the underlayment and the roof sheathing. The **textured** top side contains a rubberized polyolefin coating offering unsurpassed slip resistance. This unique, patent pending, feature provides a more secure and safer work surface.

The Nova-Seal[®] II Advantage

Nova-Seal[®] II can be left exposed for up to twelve (12) months and comes in two versions, a light beige color which stays cool in hot climates and a dark green color which absorbs sunlight on cold days and helps reduce frost in northern regions.

Nova-Seal[®] II is ideal under, asphalt shingles, cedar shakes & shingles, concrete and clay tiles, metal, slate, stone-coated metal, and synthetics. It is compatible with plywood, oriented strand board (OSB) and any available substrate.

Nova-Seal[®] II may be installed under most all roof coverings



Nova-Seal[®] II Sustainable Solution

- Nova-Seal[®] II does not support mold growth, rot or dry out as it contains no organic material and will not absorb moisture.
- Nova-Seal[®] II is 100% recyclable.
- It is far stronger and lighter than #30 felt and has much greater coverage per roll.
- Nova-Seal[®] II requires fewer nails than conventional felt underlayments.
- Nova-Seal[®] II is less costly to install than #30 felt.



www.ecpinfo.com

NOVA-SEAL^{II}[®]

Premium Roofing Underlayment

The Best Choice In Weatherproofing Systems



The Nova-Seal[®] II System Benefits

- **Exceptional Barrier Performance:** Woven Synthetic Rubber Barrier engineered with 100% synthetic polypropylene weave and modified polyolefin coatings.
- **Endurance:** The underlayment withstands prolonged exposure in all climates.
- **High Temperature Resistance:** Withstands surface temperatures up to 250°F (120°C). Won't flow or leach out at high temperatures like some asphalt felts.
- **Fire Resistance:** Meets Class A under ASTM E1098/UL790.
- **One Year Exposure Period:** Nova-Seal[®] II can remain exposed for up to one (1) year.
- **Wind Uplift Resistance:** Offers exceptional tear and puncture strength, tougher than felt in inclement weather.
- **Low Temperature Application:** Remains flexible in cold weather and will roll out without cracking or chatter when fastened.
- **Slip Resistant Textured Surface:** Coated on both sides with special slip resistant coatings that also provide a layer of toughness. The top side contains a rubber-modified polyolefin coating.



Simply the best solution to your weatherproofing needs.

Customer Service

50 Abbey Avenue | Truro, Nova Scotia | Canada B2N 6W4
800 565 2000 | info@ecpinfo.com



www.ecpinfo.com